

CLAIMS

What is claimed is:

- Sub
A1
End*
1. A microprocessor comprising:
at least one throttling mechanism; and
a thermal control subsystem to estimate an amount of power used by
said microprocessor and to control said at least one throttling mechanism
based on said estimated power usage.
2. The microprocessor of claim 1, wherein the amount of power used by
the microprocessor is estimated based on the number of occurrences of at least
one activity performed in said microprocessor.
3. The microprocessor of claim 1, wherein thermal control subsystem
includes a power usage monitoring unit which determines the number of
occurrences of at least one activity performed by the microprocessor within a
sampling time period and computes the estimated power usage based on (1)
the count value associated with said at least one activity, (2) current clock
frequency and (3) operating voltage level of the microprocessor
4. The microprocessor of claim 3, wherein the power usage monitoring
unit estimates the amount of the power used by the microprocessor by
averaging the current estimated power usage value with a defined number of
most recently estimated power usage values obtained during previous
sampling time periods.

5. The microprocessor of claim 1, wherein the thermal control subsystem further comprises a throttling control unit which compares said estimated amount of power used by the microprocessor against a threshold and activates the throttling mechanism if the estimated power used by the microprocessor is greater than said threshold or deactivates the throttling mechanism if the estimated power used by the microprocessor is less than said threshold.

6. The microprocessor of claim 1, wherein the throttling mechanism is activated in a deterministic manner by the thermal control subsystem.

7. The microprocessor of claim 2, wherein said at least one activity monitored by the thermal control subsystem comprises at least one of the following activities; (1) floating point operation, (2) cache memory access and (3) instruction decoding.

8. A method comprising:
estimating an amount of power used by a microprocessor; and
controlling at least one throttling mechanism incorporated in the microprocessor based on said estimated power usage.

9. The method of claim 8, wherein the amount of power used by the microprocessor is estimated based on the number of occurrences of at least one activity performed in the microprocessor.

10. The method of claim 8, wherein the estimating the amount of power used by the microprocessor further comprises:

counting the number of occurrences of at least one activity performed by the microprocessor within a sampling time period; and

adjusting the number of occurrences of said at least one activity according to current operating frequency and voltage level of the microprocessor.

11. The method of claim 10, wherein the estimating the amount of the power used by the microprocessor further comprises averaging the current estimated power usage value with a defined number of most recently estimated power usage values obtained during previous sampling time periods.

12. The method of claim 8, further comprising:

comparing said estimated amount of power used by the microprocessor against a threshold;

activating said at least one throttling mechanism if said estimated power used by the microprocessor is greater than said threshold; and

deactivating said at least one throttling mechanism if said estimated power used by the microprocessor is less than said threshold.

13. The method of claim 8, wherein the throttling mechanism is activated in a deterministic manner.

14. The method of claim 10, wherein said at least one activity monitored is selected from the following activities; (1) floating point operation, (2) cache memory access and (3) instruction decoding.

15. A thermal control system comprising:

a power usage estimator to estimate an amount of power used by a microprocessor based on the number of occurrences of at least one activity performed by the microprocessor during a defined time period; and

a throttling control unit to control at least one throttling mechanism incorporated in the microprocessor based on the estimated amount of power used by the microprocessor.

16. The thermal control system of claim 15, wherein said power usage estimator estimates the amount of power used by the microprocessor based on (1) the number of occurrences of at least one activity, (2) current clock frequency and (3) operating voltage level of the microprocessor.

17. The thermal control system of claim 15, further comprising a filter to adjust the estimated amount of power usage by applying recently estimated power usage values obtained during previous sampling time periods with the current estimated power usage value.

18. The thermal control system of claim 15, wherein said throttling control unit compares said estimated amount of power used by the microprocessor against a threshold and activates the throttling mechanism if the estimated power used by the microprocessor is greater than said threshold or deactivates the throttling mechanism if the estimated power used by the microprocessor is less than said threshold.

19. A machine-readable medium that provides instructions, which when executed by a microprocessor cause said microprocessor to perform operations comprising:

estimating an amount of power used by a microprocessor; and

controlling at least one throttling mechanism incorporated in the microprocessor based on said estimated power usage.

Sub
P1
and

20. The machine-readable medium of claim 19, wherein the amount of power used by the microprocessor is estimated based on the number of occurrences of at least one activity performed in the microprocessor.

21. The machine-readable medium of claim 19, wherein the operation of estimating the amount of power used by the microprocessor further comprises reading count data representing the number of occurrences of at least one activity performed by the microprocessor within a sampling time period and adjusting the number of occurrences of said at least one activity according to current operating frequency and voltage level of the microprocessor.

22. The machine-readable medium of claim 21, wherein the operation of estimating the amount of the power used by the microprocessor further comprises averaging the current estimated power usage value with a defined number of most recently estimated power usage values obtained during previous sampling time periods.

23. The machine-readable medium of claim 19, wherein the operations further comprises:

comparing said estimated amount of power used by the microprocessor against a threshold;

activating said at least one throttling mechanism if said estimated power used by the microprocessor is greater than said threshold; and
deactivating said at least one throttling mechanism if said estimated power used by the microprocessor is less than said threshold.

24. The machine-readable medium of claim 19, wherein the throttling mechanism is activated in a deterministic manner.

Sub
A1
Cont

25. The machine-readable medium of claim 21, wherein said at least one activity monitored is selected from the following activities; (1) floating point operation, (2) cache memory access and (3) instruction decoding.

continued on next page